



## QB2500

The QB2500 Fixed Felling Head is a multi-functional felling attachment designed to fell, bunch, shovel, and load. Its high torque continuous rotation system and grapple type arm fundamentals allow for highly controlled felling for large, high-value hard and soft wood, providing increased value recovery.



# QB2500

## STANDARD CONFIGURATION

## METRIC

## IMPERIAL

WEIGHTS & DIMS.	Weight	1,750 kg	3,858 lbs
	Height	1,870 mm	74"
	Depth	1,646 mm	64"
	Width ( <i>Arms Closed</i> )	1,346 mm	53"
	Width ( <i>Arms Open</i> )	1,430 mm	56"
	Rotate Motors	3 x MCR03	
	Degree of Rotation	Continuous 360°	

GRAPPLE SECTION	Minimum Closing Diameter	100 mm	4"
	Maximum Opening Diameter	680 mm	26"

SAW	Cutting Capacity	630 mm	25"
	Bar Length	838 mm	33"
	Saw Motor	F12-60	
	Motor Size	60 cc	3.66 in <sup>3</sup>
	Chain Size	19.05 mm	3/4"
	Saw Bar Rotation	225°	

HYD.	Pressure	300 bar	4,350 psi
	Maximum Flow	250 lpm	66 gpm
	Valve Bank	M4-15	

CARRIER REQS.	Carrier Size	20 – 24 ton	
---------------	--------------	-------------	--