

32-QDM 'PRELIMINARY'

Quadco's new 32-inch drum mulcher is the latest addition to a current lineup of tough, reliable and cost-efficient forestry mulching attachments. It is a versatile head, compact in dimensions but heavy duty, best suited to 8-15 ton excavators. To improve productivity and handling of ground material, a 100-degree lateral tilt is offered as standard equipment as well as a fixed heel equipped with replaceable bucket teeth. The drum is available with a variety of Quadco teeth, all-steel or carbide, to suit any application. The head will outproduce and outlive many other mass-produced brands, often built too light for professional contractors. Built-in universal boom adapter provides equipment dealers, particularly rental fleets, flexibility and quick turnarounds to meet the demands of their client's businesses - pins and sleeves only can be swapped when a change of carriers is required.



32-QDM 'PRELIMINARY'

SPECIFICATIONS

METRIC

IMPERIAL

		METRIC	IMPERIAL
WEIGHT & DIMENSIONS	Weight (<i>Incl lateral tilt, heel, typical bolt-on sleeves & pins</i>)	770 kg	1,700 lbs
	Overall Height	1,041 mm	41"
	Width	610 mm	24.5"
	Length	1,499 mm	59"
	Lateral Tilt Angle	100° (+60°/-40°)	
DRUM	Cutting Swath	813 mm	32"
	Drum Diameter, Tip-to-Tip	457 mm	18"
	Number of Teeth	18	
	Drum Speed	2,800 rpm	
HYDRAULICS	Recommended Carrier Size	8 - 15 ton	
	Variable Displacement Motor	60 or 85 cc	
	Minimum Flow @ Pressure	65 l/min @ 240 bar	17 gpm @ 3,500 psi
	Optimum Flow @ Pressure	140 l/min @ 240 bar	37 gpm @ 3,500 psi
	Maximum Pressure	340 bar	5,000 psi



QUADCO.COM | 1-800-668-3340

169 Industrial Dr.
Lexington
SC 29072

2550 N Hendrickson Dr.
Suite A, Kalama
WA 98625

66 Industriel Blvd.
Suite 113, St. Eustache
QC J7R 5C2

600 Chilcotin Rd.
Kamloops
BC V2H 1G5

3 View Road
Mangakakahi
Rotorua 3015, NZ