

QUADCO

QB3500

The QB3500 Fixed Felling Head is a multi-functional felling attachment designed to fell, bunch, shovel, and load. Its high torque continuous rotation system and grapple type arm fundamentals allow for highly controlled felling for large, high-value hard and soft wood, providing increased value recovery.





QB3500

| STANDARD CONFIGURATION | | METRIC | IMPERIAL |
|------------------------|--------------------------|-----------------|----------------------|
| WEIGHTS & DIMS. | Weight | 2,450 kg | 5,400 lbs |
| | Height | 2,150 mm | 85" |
| | Depth | 1,962 mm | 77" |
| | Width (Arms Closed) | 1,422 mm | 56" |
| | Width (Arms Open) | 1,856 mm | 73" |
| | Rotate Motors | 2 x MCR05 | |
| | Degree of Rotation | Continuous 360° | |
| GRAPPLE | Minimum Closing Diameter | 140 mm | 5.5" |
| | Maximum Opening Diameter | 1,100 mm | 43.3" |
| SAW | Cutting Capacity | 870 mm | 34" |
| | Bar Length | 1,092 mm | 43" |
| | Saw Motor | F12-60 | |
| | Motor Size | 60 cc | 3.66 in ³ |
| | Chain Size | 19.05 mm | 3/4" |
| | Saw Bar Rotation | 225° | |
| HYD. | Pressure | 300 bar | 4,350 psi |
| | Maximum Flow | 250 lpm | 66 gpm |
| | Valve Bank | M4-15 | |
| CARRIER REGS. | Carrier Size | | 24 – 28 ton |

ı