

6000V

6000V is a versatile head that has a wide range of applications, mainly focused on final felling. This unit is a further development of our best seller 6000B with improvements and updates to work even better in today's modern forestry.



6000V

STANDARD CONFIGURATION

METRIC

IMPERIAL

WEIGHTS & DIMS.	Weight	1 342 kg	2 959 lb
	Height to Felling Link	1 682 mm	66.2"
	Maximum Width (<i>With Arms Closed</i>)	1 235 mm	48.6"
	Maximum Width (<i>With Arms Open</i>)	1 682 mm	66.2"
DRIVE SECTION	Number of Drive Rollers	2	
	Motor Size (<i>Drive Arm</i>)	857 cc	52.3 in ³
	Maximum Drive Roller Opening (<i>Diameter</i>)	525 mm	20.7"
	Maximum Drive Roller Closing (<i>Diameter</i>)	12 mm	0.5"
	Feed Speed	4.6 mps	15.1 fps
DELIMB SECTION	Number of Delimb Arms	3	
	Maximum Delimb Opening	641 mm	25.2"
	Maximum Delimb Full Coverage	500 mm	19.6"
	Minimum Delimb Closing (<i>Diameter</i>)	15 mm	0.59"
BUTT SAW	Saw Type	TBD	
	Maximum Cut (<i>Diameter</i>)	65 cm 71 cm	26" 28"
	Bar Size	75 cm 82 cm	30" 32"
	Chain Pitch	0.404 pitch	
	Motor Size	19 cc	1.2 in ³