

# QS600

# ***SOUTHTAR***

The QS600 is designed for medium to large-sized wood with an optimum operating size of 22-26" in diameter. This original large multi-tree processor is packed full of design features that set it apart from the competition.



## STANDARD CONFIGURATION

## METRIC

## IMPERIAL

WEIGHTS & DIMS.	Weight ( <i>Including Rotator Top &amp; Link</i> )	3,572 kg	7,875 lbs
	Height ( <i>In Harvesting Position</i> )	3,018 mm	119"
	Maximum Width ( <i>With Head Open</i> )	2,019 mm	79.5"
	Degree of Rotation	Continuous 360°	
DRIVE SECTION	Number of Drive Rollers	4	
	Motor Size ( <i>Drive Arm</i> )	1,048 cc	
	Motor Size ( <i>Fixed Center Drive</i> )	630 cc	
	Maximum Drive Roller Opening ( <i>Diameter</i> )	1,120 mm	44"
	Maximum Drive Roller Closing ( <i>Diameter</i> )	80 mm	3.1"
	Feed Speed	4.8 – 5.7 mps	15.5 – 18.7 fps
DELIMB SECTION	Maximum Delimb Opening ( <i>Diameter</i> )	750 mm	29.5"
	Minimum Delimb Closing ( <i>Diameter</i> )	80 mm	3.1"
	2 Stem Processing +/- 1" Accuracy	300 mm	12"
	3 Stem Processing +/- 1" Accuracy	200 mm	8"
BUTT SAW	Saw Type	SS 3/4	SS 3/4
	Bar Size	965 mm	38"
	Chain Pitch	19.05 mm	3/4"
	Chain Auto Tension	Standard	
	Laser Find End	Standard	
TOP SAW	Bar Size	710 mm	28"
	Chain Pitch	10.26 mm	0.404"
CARRIER REQS.	Carrier Size ( <i>Tracked</i> )	25,000 – 30,000 kg	25 – 30 ton
	Maximum Pressure	35 mpa	5,076 psi
	Optimum Flow @ Pressure	300 – 350 lpm @ 15 mpa	79 – 93 gpm @ 2,175 psi
CONTROL SYSTEM	Full Optimization	Optional	
	Electronic Calipers ( <i>For Electronic Calibrations</i> )	Optional	
CONFIGS.	Butt Saw Chain Grease System	Optional	
	Continuous 360 Rotation	Standard	
	Startrax ( <i>Satellite Communication System</i> )	Optional	