

Quadco's 52-inch drum mower is part of our current line up of tough, reliable and productive forestry mulching attachments. It is an extreme duty attachment, best suited to 20-35 ton excavators and feller bunchers. To improve productivity and handling of ground material, a 102-degree lateral tilt is offered as standard equipment as well as a fixed heel equipped with replaceable bucket teeth. The drum has a spiral-shaped bite limiter that also spreads material evenly across the width. It is available with a variety of Quadco teeth, all-steel or carbide, to suit any application. Built-in universal boom adapter provides equipment dealers, particularly rental fleets, flexibility, and quick turn arounds to meet the demands of their client's businesses - pins and sleeves can be swapped when a change of carriers is required.



STANDARD CONFIGURATION

METRIC

IMPERIAL

WEIGHT & DIMENSIONS	Weight (<i>Incl lateral tilt, heel, typical bolt-on sleeves & pins</i>)	2,223 kg	4,900 lbs
	Overall Height	1,524 mm	60"
	Width	864 mm	34"
	Length (max. length with heel)	2,515 mm	99"
	Lateral Tilt Angle		102° (+ 52°/-50°)
DRUM	Cutting Swath	1,321 mm	52"
	Drum Diameter, Tip-to-Tip	610 mm	24"
	Number of Teeth	26	
	Drum Speed	2,200 rpm	
HYDRAULICS	Recommended Carrier Size	20 - 35 ton	
	Variable Displacement Motor	1 x 170 cc	
	Minimum Flow @ Pressure	189 l/min @ 240 bar	50 gpm @ 3,500 psi
	Optimum Flow @ Pressure	246 l/min @ 240 bar	65 gpm @ 3,500 psi
	Maximum Pressure	340 bar	5,000 psi




QMX10420X

QMX10395X

QMX10380T

QMX10384T

QMX10385T



Carbide - Rock
Extreme Impact
High Abrasion

Carbide - Planer
Reduce material size
Medium Impact
High Abrasion

Steel - Planer 4-in-1
Rotatable & Reversible
Sharpenable
Low Abrasion

Steel - Beaver
Rotatable
Viney material
Low Abrasion

Steel - Planer
Rotatable
Sharpenable
Low Abrasion