


Quadco SC models offer a larger accumulation area. This larger accumulation is highly beneficial when working in stands containing smaller stems limiting dump cycles. The two sets of arms are each moved by a single cylinder and are connected by an equalizer bar. The cast arms are contoured for maximum durability and support when accumulating. A new integrated valve is housed directly in the head, reducing the number of hoses down the boom and through the head. This design simplifies installation, even on non-dedicated forestry machines, boosting overall uptime. The ultra-reliable disc drive and Quadco disc give fast and precise cuts, with numerous tooth options available from Quadco Cutting Tools!



STANDARD CONFIGURATION

METRIC

IMPERIAL

WEIGHTS & DIMS.	Rotation 40° (<i>Medium Torque</i>)	2,180 kg	4,795 lbs
	Rotation 360° (<i>Medium Torque</i>)	2,386 kg	5,250 lbs
	Height	2,565 mm	101"
	Width	1,499 mm	59" with 1x chute
	Depth	1,499 mm	59"
	Maximum Throat Opening	1,219 mm	48"
	Maximum Throat Opening @ Teeth	908 mm	35.75"
	Accumulation Area (<i>Over Blade</i>)	0.39 m ²	4.2 ft ²
DISC	Cutting Capacity	508 mm	20"
	Tip-to-Tip Diameter	1,321 mm	52"
	Rated Saw Speed	1,250 rpm	
	Number of Teeth	18	
	Saw Kerf	51 mm	2"
	Weight (<i> HOLDERS & TEETH Varies Depending on Disc</i>)	264 kg	580 lbs
	Style (<i>One Piece or Segmented</i>)	One Piece	
HYD.	Grab Arms	1 Cylinder	
	Accumulating Arms	1 Cylinder	